

215

Dual 15-Band graphic Equalizer

dbx[®]
PROFESSIONAL PRODUCTS

VISIONARY DESIGN

The dbx 2 Series Graphic Equalizers have been designed to meet the needs of the most demanding sound reinforcement environments, while offering the simplicity of straight forward controls. The 215 not only provides standard features like dual channels, 15 2/3 octave bands, ISO frequency centers, +/-12 dB input gain range, and switchable 50Hz/12 dB per octave low-cut filters, but also includes other thoughtful features. These features include: 20 mm faders; selectable +/-6dB or +/-12dB boost/cut range for precise gain adjustments; XLR, and 1/4" TRS connectors for installation ease; balanced inputs and outputs for quiet operation; and chassis/signal ground lift capabilities for quick hum isolation. The visionary design of the dbx 2 Series has been pursued to make your job easier.

REVOLUTIONARY ENGINEERING

The 2-Series represents a major step forward in the performance of entry-level graphic equalizers. From its amazing 10Hz to 50kHz frequency response, to its 108dB dynamic range, internal toroidal transformer, the 2-Series offers out of this world specifications with a down to earth price point. Sure to find a home in the studio, on tour and with installed sound venues, the 2-Series is destined to take its rightful place in the lineage of great dbx[®] signal processors that are the Professional's Choice[™]. With such affordable quality, there's no longer any excuse for compromising your sound.

FEATURES

- **Two 15-band, 2/3-octave Constant Q frequency bands (215)**
- **Switchable boost/cut ranges of ±6 or ±12 dB**
- **12 dB per octave low-cut filter**
- **Front panel bypass switch**
- **±12 dB input gain range**
- **4-segment LED ladders for monitoring output levels-the most accurate visual feedback available**
- **XLR and TRS Inputs and Outputs**
- **Internal Toroidal Transformer**
- **Frequency Response of <10 Hz to >50kHz**
- **Dynamic range of greater than 108dB**
- **Designed and Built in the USA**

8760 S. Sandy Pkwy.
Sandy, Utah 84070
Phone (801) 568-7660
Fax (801) 568-7662
Int'l Fax (801) 568-7583
customer@dbxpro.com
http://www.dbxpro.com

H A Harman International Company

18-0115-A 7/02



215

Dual Channel 15-Band Graphic Equalizer



SPECIFICATIONS

Inputs

Connectors: 1/4" TRS, female XLR (pin 2 hot)
Type: Electronically balanced/unbalanced, RF filtered
Impedance: Balanced 40k Ω , unbalanced 20k Ω
Max Input Level: >+21dBu balanced or unbalanced
CMRR: >40dB, typically >55dB at 1kHz

Outputs

Connectors: 1/4" TRS, male XLR (pin 2 hot)
Type: Impedance-balanced/unbalanced, RF filtered
Impedance: Balanced 100 Ω , unbalanced 50 Ω
Max Output Level: >+21dBu balanced/unbalanced into 2k Ω or greater
>+18dBm balanced/unbalanced (into 600 Ω)

System Performance

Bandwidth: 20Hz to 20kHz, +0.5/-1dB
Frequency Response: <10Hz to >50kHz, +0.5/-3dB

Dynamic Range: 108db
Signal-to-Noise: 90db
THD+Noise: <0.004%
Interchannel Crosstalk:<-80dB, 20Hz to 20kHz

Function Switches

EQ Bypass: Bypasses the graphic equalizer section in the signal path
Low Cut (recessed): Activates the 40Hz 18dB/octave high-pass filter
Range (recessed): Selects either +/- 6dB or +/- 12dB slider boost/cut range

Power Supply

Operating Voltage: 100VAC 50/60Hz, 120VAC 60Hz, 230VAC 50/60Hz
Power Consumption: 24W
Mains Connection: IEC receptacle

Note: Specifications subject to change.

dbx engineers are constantly working to improve the quality of our products. Specifications are, therefore subject to change without notice.

FOR MORE INFORMATION CONTACT:

dbx Professional Products
8760 S. Sandy Pkwy.
Sandy, Utah 84070
Phone (801) 568-7660
Fax (801) 568-7662
customer@dbxpro.com
<http://www.dbxpro.com>

dbx PROFESSIONAL PRODUCTS

The Professional's Choice In Signal Processing

A Harman International Company